

# Jeremadra Series

[AES-12-REWL1042]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	2W, 4W, TBC
Efficacy	60lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
IP Rating	65, TBC
IK Rating	08

ATTRIBUTE	VALUES
Voltage	DC 24V
Light Source & Brand	LED: Osram SMD
Size - Length	Length: 171mmL
Size - Width	Width: 106mmW
Size - Height	Height: 65mmH
Cut Out Size - Length	Cut Out: 160mmL
Cut Out Size - Width	Mounting Sleeve: 98mmW
Cut Out Size - Height	Cut Out: 85mmH
Trim / Outer Colour	Trim/Outer: Black, Trim/Outer: Silver
Mounting Options	TBC, Wall Mounted
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K, CCT: RGB
Accessories	DMX Controls
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 171mmL
Size - Height	Height: 65mmH
Cut Out Size - Length	Cut Out: 160mmL
Cut Out Size - Width	Mounting Sleeve: 98mmW
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

