

Sandalwood Series - S

[AES-12-LSL116S]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | 6W, TBC |
| Efficacy | 60lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| IP Rating | 65, TBC |
| IK Rating | 08 |
| Voltage | DC 24V |
| Light Source & Brand | LED: Osram SMD |
| Size - Length | Length: 150mmL |
| Size - Width | Width: 150mmW |
| Size - Height | Height: 36mmH |
| Trim / Outer Colour | Trim/Outer: Black, Trim/Outer: Silver, Trim/Outer: Dark Grey |
| Mounting Options | TBC, Wall Mounted |
| Beam Angle | TBC, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2200K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K, CCT: RGB |
| Accessories | DMX Controls |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Length | Length: 150mmL |
| Size - Height | Height: 36mmH |
| Beam Angle | TBC, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Accessories | DMX Controls |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

