

Aeroglen Series - 36

[AES-12-WM1080136]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 20W, 30W, 32W, 36W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3

ATTRIBUTE	VALUES
IP Rating	65, TBC
IK Rating	08
Voltage	AC220-240V
Light Source & Brand	LED: Cree COB
Size - Diameter	Diameter: 108mmØ
Size - Length	Length: 890mmL, Length: 390mmL, Length: 1090mmL, Length: 590mmL
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Mounting Options	TBC, Wall Mounted
Beam Angle	TBC, Beam Angle: 10°, Beam Angle: 23°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K, CCT: RGB
Accessories	DMX Controls
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C
Lifetime	Reported L80 @ 85° >63,500 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 108mmØ
Size - Length	Length: 890mmL, Length: 390mmL, Length: 1090mmL, Length: 590mmL
Beam Angle	TBC, Beam Angle: 10°, Beam Angle: 23°, Beam Angle: 38°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

