

Aeroglen Duo Series - SMD

[AES-12-WM10812]



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | TBC, 2 x 15W (30W), 2 x 20W (40W), 2 x 25W (50W), 2 x 30W (60W) |
| Efficacy | 90lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <5, <3 |
| IP Rating | 65, TBC |
| IK Rating | 08 |
| Voltage | DC 24V |
| Light Source & Brand | LED: Osram SMD |
| Size - Diameter | Diameter: 108mmØ |
| Size - Width | Width: 563mmW |
| Size - Length | Length: 890mmL, Length: 390mmL, Length: 1090mmL, Length: 590mmL |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey |
| Mounting Options | TBC, Wall Mounted |
| Beam Angle | TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2200K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K, CCT: RGB |
| Accessories | DMX Controls |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------|--------|
|-----------|--------|

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 108mmØ |
| Size - Length | Length: 890mmL, Length: 390mmL, Length: 1090mmL, Length: 590mmL |
| Beam Angle | TBC, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 20°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Accessories | DMX Controls |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

