

Dalyston Series - 30-50W



Technical Specifications

ATTRIBUTE	VALUES
Wattages	30W, 50W
Efficacy	125lm/W
Correlated Colour Index (CRI)	CRI: >80
MacAdam Ellipse (SDCM)	SDCM: <6
IP Rating	IP65
IK Rating	IK10
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: SMD 3030
Driver	Driver: SOSEN
Size - Length	Length: 207mmL
Size - Width	Width: 200mmW
Size - Height	Height: 108mmH
Weight	Weight: 2.13kg
Tilt	Tilt: 90°
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -20°C to +50°C
Trim / Outer Colour	Trim/Outer: Black, Trim/Outer: Bronze
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5700K
Mounting Options	Wall Mounted
Accessories	Build-In Sensor, External Sensor
Lifetime	Reported L80 @ 85° >70,000 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

Product Options

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Size - Length	Length: 207mmL
Size - Height	Height: 108mmH
Beam Angle	Beam Angle: 120°
Dimming Options	Non-Dimmable, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +50°C
Accessories	Build-In Sensor, External Sensor

Certification and Compliance

