

Palmer Series - 1000



Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, 13W, TBC, 15W
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	65, TBC
IK Rating	08
Voltage	AC220-240V
Light Source & Brand	LED: Osram SMD, LED: CREE SMD
Size - Diameter	Diameter: 150mmØ
Size - Height	Height: 1000mmH

ATTRIBUTE	VALUES
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 150mmØ
Size - Height	Height: 1000mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +50°C

Certification and Compliance

