

Belgrave EdgeLit Series 6030

[AES-08-B6030]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	10W, 12W, TBC, 14W, 16W, 18W, 20W, 22W, 24W, 26W, 28W, 30W
Efficacy	100lm/W, 110lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<4, <3
IP Rating	20, TBC
IK Rating	06
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: San'an SMD 2835
Driver	Driver: BOKE
Size - Length	Length: 596mmL
Size - Width	Width: 296mmW
Size - Height	Height: 11mmH
Weight	Weight: 1.89kg
Beam Angle	TBC, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: PMMA
Corrosion Resistance	Corrosion Resistance: C4
Operating Temperature	Operating Temperature: -30°C to +40°C
Trim / Outer Colour	Trim/Outer: White
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Surface Mounted, TBC, T-Bar Recessed, Plaster Recessed
Lens Options	TBC, Frosted PMMA Lens, MicroPrismatic Diffuser
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 596mmL
Size - Height	Height: 11mmH

ATTRIBUTE	VALUES
Beam Angle	TBC, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -30°C to +40°C

Certification and Compliance

