

Padbury Series



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|------------------|
| Wattages | 10W, TBC, 20W |
| Efficacy | 80lm/W |
| Correlated Colour Index (CRI) | >80, TBC |
| IP Rating | 65, TBC |
| IK Rating | 10 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Epistar SMD |

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Size - Length | Length: 220mmL, Length: 280mmL |
| Size - Width | Width: 135mmW, Width: 180mmW |
| Size - Height | Height: 70mmH, Height: 83mmH |
| Mounting Options | Surface Mounted, TBC, Wall Mounted, Ceiling Mounted |
| Beam Angle | TBC, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 1-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 6000K |
| Accessories | Microwave Sensor, PIR Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency |
| Trim / Outer Colour | Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey |
| Material of Housing | Housing Material: Aluminium |

Product Options

| ATTRIBUTE | VALUES |
|---------------------|--|
| Size - Length | Length: 220mmL, Length: 280mmL |
| Size - Height | Height: 70mmH, Height: 83mmH |
| Beam Angle | TBC, Beam Angle: 120° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 1-10V Dimmable, DALI Dimmable |
| Accessories | Microwave Sensor, PIR Sensor, Dimming Sensor (0%-100%-25%-10%-0%), Emergency |
| Material of Housing | Housing Material: Aluminium |

Certification and Compliance

