

## Saddleworth Series



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 20W, 30W, 40W
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, TBC
IP Rating	65, TBC
IK Rating	10
Light Source & Brand	LED: Epistar SMD
Size - Length	Length: 300mmL
Size - Width	Width: 300mmW
Size - Height	Height: 90mmH
Mounting Options	Surface Mounted, TBC, Wall Mounted, Ceiling Mounted
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 6000K
Accessories	Dimming Sensor (0%-100%-25%-10%-0%), 0-100% Sensor
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Material of Housing	Housing Material: Aluminium

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 300mmL
Size - Height	Height: 90mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Accessories	Dimming Sensor (0%-100%-25%-10%-0%), 0-100% Sensor
Material of Housing	Housing Material: Aluminium

## Certification and Compliance

