

Leeville Series - 100



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|---------------------------|
| Wattages | TBC, 2 x 12W (24W) |
| Efficacy | 80lm/W |
| Correlated Colour Index (CRI) | >80, TBC |
| IP Rating | 65, TBC |
| IK Rating | 08 |
| Voltage | AC220-240V |
| Driver | Driver: Integrated Driver |
| Size - Diameter | Diameter: 108mmØ |
| Size - Height | Height: 260mmH |
| Mounting Options | TBC, Wall Mounted |
| Beam Angle | TBC, Beam Angle: 40° |

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 3000K |
| Lens Options | TBC, Tempered Glass Lens |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -30°C to +45°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 108mmØ |
| Size - Height | Height: 260mmH |
| Beam Angle | TBC, Beam Angle: 40° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -30°C to +45°C |

Certification and Compliance

