

Tahara Series - 900



Technical Specifications

ATTRIBUTE	VALUES
Wattages	2, 4, 6, 8, 10W, 12W, TBC, 14W, 16W, 18W, 20W, 22W, 24W, 26W, 28W, 30W
Efficacy	120lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	67, TBC
IK Rating	08
Voltage	AC100-277V, 50/60Hz
Light Source & Brand	LED: SMD 2835
Driver	Driver: MFU28D-40P
Size - Length	Length: 900mmL
Size - Width	Width: 99.76mmW
Size - Height	Height: 75.77mmH
Weight	Weight: 1.45kg
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Corrosion Resistance	Corrosion Resistance: C5
Operating Temperature	Operating Temperature: -20°C to +50°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: White
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 5700K
Mounting Options	TBC, Ceiling Mounted
Accessories	Emergency, Motion Sensor
Lens Options	TBC, 120D
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
-----------	--------

ATTRIBUTE	VALUES
Size - Length	Length: 900mmL
Size - Height	Height: 75.77mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +50°C
Accessories	Emergency, Motion Sensor

Certification and Compliance

