

Padthaway Series - 1500



Technical Specifications

ATTRIBUTE	VALUES
Size - Length	Length: 1500mmL
Wattages	28W, 30W, 32W, 34W, 36W, 38W, 40W, 42W, 44W, 46W, 48W, 50W, 52W, 54W, 56W
Efficacy	140lm/W, 160lm/W
Correlated Colour Index (CRI)	CRI: >80
IP Rating	IP65
IK Rating	IK08
MacAdam Ellipse (SDCM)	SDCM: <5
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: BOKE

ATTRIBUTE	VALUES
Size - Width	Width: 65mmW
Size - Height	Height: 55mmH
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Mounting Options	Surface Mounted, Suspended
Beam Angle	Beam Angle: 120°
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit
Material of Housing	Housing Material: Aluminium
Material of Optics	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Weight	Weight: 14.5kg

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1500mmL
Size - Height	Height: 55mmH
Dimming Options	Non-Dimmable, 1-10V Dimmable, DALI Dimmable
Beam Angle	Beam Angle: 120°
Accessories	Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

