

Padthaway Series - 1800



Technical Specifications

ATTRIBUTE	VALUES
Size - Length	Length: 1800mmL
Wattages	TBC, 32W, 34W, 36W, 38W, 40W, 42W, 44W, 46W, 48W, 50W, 52W, 54W, 56W, 58W, 60W, 62W, 65W
Efficacy	140lm/W, 160lm/W
Correlated Colour Index (CRI)	>80, TBC
IP Rating	65, TBC
IK Rating	08
MacAdam Ellipse (SDCM)	<5
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: BOKE
Size - Width	Width: 65mmW

ATTRIBUTE	VALUES
Size - Height	Height: 55mmH
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Mounting Options	Surface Mounted, Suspended, TBC
Beam Angle	TBC, Beam Angle: 120°
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit
Material of Housing	Housing Material: Aluminium
Material of Optics- Glare control	Optics Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C
Weight	Weight: 24kg

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1800mmL
Size - Height	Height: 55mmH
Dimming Options	Non-Dimmable, TBC, 1-10V Dimmable, DALI Dimmable
Beam Angle	TBC, Beam Angle: 120°
Accessories	Microwave Sensor, CCT Selectable Switch, 1.2m Suspension Kit, 2.4m Suspension Kit
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -15°C to 40°C

Certification and Compliance

