

Gainsford Series - 1500



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Wattages | 25W, 50W |
| Efficacy | 120lm/W, 140lm/W, 160lm/W |
| Correlated Colour Index (CRI) | CRI: >80 |
| MacAdam Ellipse (SDCM) | SDCM: <5 |
| IP Rating | IP40 |
| IK Rating | IK04 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: SMD |
| Driver | Driver: BOKE |
| Size - Length | Length: 1500mmL |
| Size - Width | Width: 152mmW |
| Size - Height | Height: 77mmH |
| Weight | Weight: 11.2kg |
| Trim / Outer Colour | Trim/Outer: White |
| Mounting Options | Surface Mounted, Suspended |
| Beam Angle | Beam Angle: 120° |
| Dimming Options | Non-Dimmable, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 3CCT: 3000K+4000K+5000K |
| Accessories | Microwave Sensor |
| Material of Housing | Housing Material: Frosted Polycarbonate Diffuser |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------|---|
| Size - Length | Length: 1500mmL |
| Size - Height | Height: 77mmH |
| Beam Angle | Beam Angle: 120° |
| Dimming Options | Non-Dimmable, 0-10V Dimmable, DALI Dimmable |
| Accessories | Microwave Sensor |

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Material of Housing | Housing Material: Frosted Polycarbonate Diffuser |
| Operating Temperature | Operating Temperature: -15°C to 40°C |

Certification and Compliance

