

## Waaia Series - 1500 x 29W



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 29W
Efficacy	120lm/W, 140lm/W, 160lm/W
Correlated Colour Index (CRI)	>80, TBC
MacAdam Ellipse (SDCM)	<5
IP Rating	40, TBC
IK Rating	04
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Driver	Driver: Osram
Size - Length	Length: 1500mmL
Size - Width	Width: 55mmW
Size - Height	Height: 59mmH
Trim / Outer Colour	Trim/Outer: White
Mounting Options	Surface Mounted, Suspended, TBC
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K
Accessories	Microwave Sensor, CCT Selectable Switch
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1500mmL
Size - Height	Height: 59mmH
Beam Angle	TBC, Beam Angle: 120°
Dimming Options	Non-Dimmable, TBC, DALI Dimmable
Accessories	Microwave Sensor, CCT Selectable Switch
Material of Housing	Housing Material: Polycarbonate
Operating Temperature	Operating Temperature: -15°C to 40°C

## Certification and Compliance

