

# Farley Series - Up/Down

[AES-01-WP15-UD]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 2 x 10W (20W), 2 x 20W (40W)
Efficacy	120lm/W
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	66, TBC
IK Rating	08
Voltage	AC220-240V
Light Source & Brand	LED: SMD
Size - Length	Length: 150mmL

ATTRIBUTE	VALUES
Size - Width	Width: 120mmW
Size - Height	Height: 215mmH
Mounting Options	TBC, Wall Mounted
Trim / Outer Colour	Trim/Outer: White, Trim/Outer: Black, Trim/Outer: Grey
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2200K, CCT: 3000K, CCT: 3500K, CCT: 4000K, CCT: 5000K, CCT: 6500K, CCT: RGB
Accessories	DMX Controls
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 150mmL
Size - Height	Height: 215mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

