

Hunter Series - 195

[AES-12-GL0302]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	6W, 9W, TBC

ATTRIBUTE	VALUES
Efficacy	90lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	67, TBC
IK Rating	09
Voltage	AC220-240V, DC 24V
Light Source & Brand	LED: Osram SMD, LED: CREE SMD
Size - Length	Length: 195mmL
Size - Width	Width: 63mmW
Size - Height	Height: 90mmH
Cut Out Size - Length	Cut Out: 180mmL
Cut Out Size - Width	Mounting Sleeve: 58mmW
Mounting Options	Surface Mounted, TBC, Recessed
Beam Angle	TBC, Beam Angle: 10°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 45° x 35°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls
Lens Options	TBC, PMMA + Anti-UV Lens
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 195mmL
Size - Height	Height: 90mmH
Cut Out Size - Length	Cut Out: 180mmL
Cut Out Size - Width	Mounting Sleeve: 58mmW
Beam Angle	TBC, Beam Angle: 10°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 45° x 35°

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

