

Longford Series - 130



Technical Specifications

| ATTRIBUTE | VALUES |
|-------------------------------|--------------------|
| Wattages | 8W, 10W |
| Efficacy | 90lm/W |
| Correlated Colour Index (CRI) | CRI: >80, CRI: >90 |
| MacAdam Ellipse (SDCM) | SDCM: <5, SDCM: <3 |
| IP Rating | IP67 |
| IK Rating | IK09 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Cree COB |
| Size - Diameter | Diameter: 135mmØ |
| Size - Height | Height: 144mmH |
| Mounting Options | Recessed |

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Beam Angle | Beam Angle: 11° x 24°, 22° x 30°, 38° x 51°, 47° x 50° (Reflector Cup), Beam Angle: 15°, 24°, 36°, 60° (Lens) |
| Dimming Options | Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW |
| Accessories | DMX Controls |
| Lens Options | PMMA + Anti-UV Lens |
| Material of Housing | Housing Material: Stainless Steel |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|---|
| Size - Diameter | Diameter: 135mmØ |
| Size - Height | Height: 144mmH |
| Beam Angle | Beam Angle: 11° x 24°, 22° x 30°, 38° x 51°, 47° x 50° (Reflector Cup), Beam Angle: 15°, 24°, 36°, 60° (Lens) |
| Dimming Options | Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable |
| Accessories | DMX Controls |
| Material of Housing | Housing Material: Stainless Steel |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

