

Dandaloo Series - 150



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 90W, 120W, 150W
Efficacy	180lm/W, 200lm/W
IP Rating	65, TBC
IK Rating	08
Voltage	AC220-240V
Size - Diameter	Diameter: 325mmØ
Size - Height	Height: 140mmH
Beam Angle	TBC, Beam Angle: 85°, Beam Angle: 90°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K
Accessories	Microwave Sensor, Suspension Kit, PIR Sensor, PC diffuser with cover for 150-200W, 90° black ALU diffuser for 150-200W only, 65° ALU reflector for 150-200W only

ATTRIBUTE	VALUES
Weight	Weight: 2.5kg

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 325mmØ
Size - Height	Height: 140mmH
Beam Angle	TBC, Beam Angle: 85°, Beam Angle: 90°
Dimming Options	Non-Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	Microwave Sensor, Suspension Kit, PIR Sensor, PC diffuser with cover for 150-200W, 90° black ALU diffuser for 150-200W only, 65° ALU reflector for 150-200W only

Certification and Compliance

