

Longford Series - 160

[AES-12-DIL1600115]



Technical Specifications

| ATTRIBUTE | VALUES |
|-----------|--------------------|
| Wattages | TBC, 15W, 16W, 18W |
| Efficacy | 90lm/W |

| ATTRIBUTE | VALUES |
|-------------------------------------|---|
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <5, <3 |
| IP Rating | 67, TBC |
| IK Rating | 09 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Cree COB |
| Size - Diameter | Diameter: 160mmØ |
| Size - Height | Height: 157mmH |
| Mounting Options | TBC, Recessed |
| Beam Angle | TBC, Beam Angle: 11° x 24°, 22° x 30°, 38° x 51°, 47° x 50° (Reflector Cup), Beam Angle: 15°, 24°, 36°, 60° (Lens) |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW |
| Accessories | DMX Controls |
| Lens Options | TBC, PMMA + Anti-UV Lens |
| Material of Housing | Housing Material: Stainless Steel |
| Operating Temperature | Operating Temperature: -20°C to +40°C |
| Lifetime | Reported L80 @ 85° >63,500 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes |

Product Options

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Size - Diameter | Diameter: 160mmØ |
| Size - Height | Height: 157mmH |
| Beam Angle | TBC, Beam Angle: 11° x 24°, 22° x 30°, 38° x 51°, 47° x 50° (Reflector Cup), Beam Angle: 15°, 24°, 36°, 60° (Lens) |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Accessories | DMX Controls |
| Material of Housing | Housing Material: Stainless Steel |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

