

Goshen Series - 200



Technical Specifications

ATTRIBUTE	VALUES
Wattages	36W, 38W, 40W, 42W
Efficacy	80lm/W

ATTRIBUTE	VALUES
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <5, SDCM: <3
IP Rating	IP67
IK Rating	IK09
Voltage	AC220-240V
Size - Diameter	Diameter: 208mmØ
Size - Height	Height: 185mmH
Mounting Options	Recessed
Beam Angle	Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 15°, Beam Angle: 20°, Beam Angle: 24°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 36°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls
Lens Options	PMMA + Anti-UV Lens
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 208mmØ
Size - Height	Height: 185mmH
Beam Angle	Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 15°, Beam Angle: 20°, Beam Angle: 24°, Beam Angle: 25°, Beam Angle: 30°, Beam Angle: 36°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 22°, Beam Angle: 15° x 55°, Beam Angle: 20° x 60°

ATTRIBUTE	VALUES
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls
Material of Housing	Housing Material: Stainless Steel
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

