

Belgrave EdgeLit IP65 Series 1260

[AES-08-IP-B1260]



Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 20W, 22W, 24W, 26W, 28W, 30W, 32W, 34W, 36W, 38W, 40W, 44W, 46W, 48W, 50W, 52W, 54W, 56W, 58W, 60W, 62W, 64W, 66W, 68W, 70W, 72W
Efficacy	100lm/W, 110lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<4, <3
IP Rating	65, TBC
IK Rating	06
Voltage	AC220-240V, 50/60Hz
Light Source & Brand	LED: San'an SMD 2835
Driver	Driver: BOKE
Size - Length	Length: 1196mmL
Size - Width	Width: 596mmW
Size - Height	Height: 11mmH
Weight	Weight: 7.36kg
Beam Angle	TBC, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Material of Optics-Glare control	Optics Material: PMMA
Corrosion Resistance	Corrosion Resistance: C4
Operating Temperature	Operating Temperature: -20°C to +45°C
Trim / Outer Colour	Trim/Outer: White
Reflector / Internal Colour	Reflector/Internal: Opal
Correlated Colour Temperature (CCT)	CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 3CCT: 3000K+4000K+5000K
Mounting Options	Surface Mounted, TBC, T-Bar Recessed, Plaster Recessed
Lens Options	TBC, Frosted PMMA Lens, MicroPrismatic Diffuser
Lamp Life	Lamp Life: L80 B10 @ 4K, CRI80

Product Options

ATTRIBUTE	VALUES
Size - Length	Length: 1196mmL
Size - Height	Height: 11mmH
Beam Angle	TBC, Beam Angle: 90°, Beam Angle: 120°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +45°C

Certification and Compliance

