

# Bayles Series - 250

[AES-12-IGWD3602]



## Technical Specifications

ATTRIBUTE	VALUES
Wattages	TBC, 72W

ATTRIBUTE	VALUES
Efficacy	80lm/W
Correlated Colour Index (CRI)	>80, >90, TBC
MacAdam Ellipse (SDCM)	<5, <3
IP Rating	67, TBC
IK Rating	09
Voltage	AC220-240V
Light Source & Brand	LED: CREE SMD
Size - Diameter	Diameter: 250mmØ
Size - Height	Height: 162mmH
Mounting Options	TBC, Recessed
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 45°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls
Lens Options	TBC, PMMA + Anti-UV Lens
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +45°C
Lifetime	Reported L80 @ 85° >90,700 Hrs - As outlined within IESNA Standards, Projected Lifetime can be up to 6 x the reported lifetimes

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 250mmØ
Size - Height	Height: 162mmH
Beam Angle	TBC, Beam Angle: 15°, Beam Angle: 30°, Beam Angle: 45°, Beam Angle: 60°, Beam Angle: 10° x 60°, Beam Angle: 20° x 45°
Dimming Options	Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls
Material of Housing	Housing Material: Aluminium

ATTRIBUTE	VALUES
Operating Temperature	Operating Temperature: -20°C to +45°C

## Certification and Compliance

