

## Estella Series - 30



### Technical Specifications

ATTRIBUTE	VALUES
Wattages	1W, 1.5W

03 8761 6734 [accounts@ausecotech.com.au](mailto:accounts@ausecotech.com.au) <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
Efficacy	90lm/W, 100lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <5, SDCM: <3
IP Rating	IP67
IK Rating	IK08
Voltage	AC220-240V
Light Source & Brand	LED: Osram SMD, LED: CREE SMD
Size - Diameter	Diameter: 38mmØ
Size - Height	Height: 75mmH
Mounting Options	Recessed
Beam Angle	Beam Angle: 12°, Beam Angle: 25°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls, Honeycomb Optics, Half Moon Baffle Plate
Lens Options	PMMA + Anti-UV Lens
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 38mmØ
Size - Height	Height: 75mmH
Beam Angle	Beam Angle: 12°, Beam Angle: 25°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls, Honeycomb Optics, Half Moon Baffle Plate
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

## Certification and Compliance

