

Estella Series - 50



Technical Specifications

ATTRIBUTE	VALUES
Wattages	2W, 2.2W, 3W

03 8761 6734 accounts@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

ATTRIBUTE	VALUES
Efficacy	90lm/W, 100lm/W
Correlated Colour Index (CRI)	CRI: >80, CRI: >90
MacAdam Ellipse (SDCM)	SDCM: <5, SDCM: <3
IP Rating	IP67
IK Rating	IK08
Light Source & Brand	LED: Osram SMD, LED: CREE SMD, LED: Cree COB, LED: Osram COB
Size - Diameter	Diameter: 52mmØ
Size - Height	Height: 75mmH
Mounting Options	Recessed
Beam Angle	Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 25°, Beam Angle: 36°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Correlated Colour Temperature (CCT)	CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW
Accessories	DMX Controls, Honeycomb Optics, Half Moon Baffle Plate
Lens Options	PMMA + Anti-UV Lens
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Product Options

ATTRIBUTE	VALUES
Size - Diameter	Diameter: 52mmØ
Size - Height	Height: 75mmH
Beam Angle	Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 24°, Beam Angle: 25°, Beam Angle: 36°, Beam Angle: 40°, Beam Angle: 60°
Dimming Options	Non-Dimmable, Triac Dimmable, 0-10V Dimmable, DALI Dimmable
Accessories	DMX Controls, Honeycomb Optics, Half Moon Baffle Plate
Material of Housing	Housing Material: Aluminium
Operating Temperature	Operating Temperature: -20°C to +40°C

Certification and Compliance

