

Estella Series - 100



Technical Specifications

| ATTRIBUTE | VALUES |
|-----------|--------------|
| Wattages | 8W, 10W, TBC |

03 8761 6734 sales@ausecotech.com.au <http://ausecotech.com.au> 62 487 717 179

| ATTRIBUTE | VALUES |
|-------------------------------------|--|
| Efficacy | 80lm/W, 90lm/W, 100lm/W |
| Correlated Colour Index (CRI) | >80, >90, TBC |
| MacAdam Ellipse (SDCM) | <5, <3 |
| IP Rating | 67, TBC |
| IK Rating | 08 |
| Voltage | AC220-240V |
| Light Source & Brand | LED: Osram SMD, LED: CREE SMD, LED: Cree COB, LED: Osram COB |
| Size - Diameter | Diameter: 100mmØ |
| Size - Height | Height: 115mmH |
| Mounting Options | TBC, Recessed |
| Beam Angle | TBC, Beam Angle: 3°, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 25°, Beam Angle: 38°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Correlated Colour Temperature (CCT) | CCT: 2700K, CCT: 3000K, CCT: 4000K, CCT: 5000K, CCT: 6000K, CCT: 6500K, CCT: RGB, CCT: RGBW |
| Accessories | DMX Controls |
| Lens Options | TBC, PMMA + Anti-UV Lens |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Product Options

| ATTRIBUTE | VALUES |
|-----------------|------------------|
| Size - Diameter | Diameter: 100mmØ |
| Size - Height | Height: 115mmH |

| ATTRIBUTE | VALUES |
|-----------------------|--|
| Beam Angle | TBC, Beam Angle: 3°, Beam Angle: 5°, Beam Angle: 8°, Beam Angle: 10°, Beam Angle: 12°, Beam Angle: 15°, Beam Angle: 24°, Beam Angle: 25°, Beam Angle: 38°, Beam Angle: 40°, Beam Angle: 45°, Beam Angle: 60° |
| Dimming Options | Non-Dimmable, Triac Dimmable, TBC, 0-10V Dimmable, DALI Dimmable |
| Accessories | DMX Controls |
| Material of Housing | Housing Material: Aluminium |
| Operating Temperature | Operating Temperature: -20°C to +40°C |

Certification and Compliance

